

## Profile SFR-4

### HTMTSL

### CHINA

#### GENERAL INFORMATION

NAME OF THE FACILITY High Temperature Mass Transfer Sodium Loop  
ACRONYM HTMTSL  
COOLANT(S) OF THE FACILITY SODIUM  
LOCATION (address): China Institute of Atomic Energy(CIAE), P.O.Box 275 (34), 102413, Beijing, China  
OPERATOR CIAE  
CONTACT PERSON LONG Bin, P.O.Box 275 (34), 102413, Beijing, China, Department of Fast Reactor Research and Design, [Tel:+86-10-69357613](tel:+86-10-69357613) , Email:bin.long@hotmail.com; binlong@ciae.ac.cn  
email):

STATUS OF THE FACILITY Standby  
Start of operation (date): 2000

MAIN RESEARCH FIELD(S)

- Zero power facility for V&V and licensing purposes
- Design Basis Accidents (DBA) and Design Extended Conditions (DEC)
- Thermal-hydraulics
- Coolant chemistry
- Materials
- Systems and components
- Instrumentation & ISI&R

#### TECHNICAL DESCRIPTION

##### Description of the facility

High temperature mass transfer sodium loop (HTMTSL) is a pump-drive un-isothermal test facility to study the carbon transfer effect of steels which were used for primary and(or) secondary loops in sodium-cooled fast reactor (SFR). Simulation corrosion tests of SFR structural materials at different test conditions can be performed in this loop.

HTMTSL basically consists of a main circuit with double test sections (i.e. a hot leg and a cold) which could hold around 50 pieces coupon, sodium purification system, cover gas system and instrumentation and control system. The main components and its technical parameter are listed as following:

**Test section:** it consists of two test sections, one is located at high temperature area, and the other is at low temperature part. FIG. 1 shows the structure diagram of test section. It was made of austenitic steel 316 S.S. tubes with  $\phi 50\text{mm} \times 3\text{mm}$ , the length of test section is about 600mm. The free surface of hot sodium was covered by argon gas.




FIG. 1. Schematic of test section

Surge tank: surge tank locates at the highest position of the loop which could provide expansion space for sodium during the melting. FIG. .2 shows the structure of surge tank. The tank volume is about  $0.03\text{m}^3$ , and the structure material is 316 S.S. The coupons could be placed here to perform corrosion test at lower sodium velocity.




FIG. 2. Schematic of surge tank

**Heating system:** it consists of a heater and auxiliary heater. The total power for this system is about 12 KW

**Intermediate heat exchanger (IHX):** U-shape IHX was used as the heat exchange in the loop. FIG. .3 shows the structure of this IHX. The hot sodium goes through the outer casing while cold sodium flowing in the inner tube. The diameters of outer casing and inner tube are  $\phi 25$  and  $\phi 14\text{mm}$ , respectively. The heat transfer area is about  $96\text{ cm}^2$ . The temperature different between inlet and outlet is about  $30\text{-}50^\circ\text{C}$ .




FIG. 3. Schematic of IHX

**Electromagnetic pump for main circuit:** EM pump is "the heart" of circuit system, which drives the sodium flowing in the loop. FIG. 4 is the picture of the EM pump. The main parameters of the pump are listed as following:

**Type:** air cooling type single-phase electromagnetic pump

**Pump head:** >0.2 MPa

**Nominal flow:** 5 m<sup>3</sup>/h

**Maximum temperature:** 550°C



FIG. 4. EM pump for main circuit

**Flow meter:** permanent magnetic flow meter was used in the loop, flow range is 5 m<sup>3</sup>/h, the maximum working temperature is 600°C, and the error is 0.018 m<sup>3</sup>/h.

**Purification system:** The sodium need to be purified after it was loaded into the loop because the corrosion products, leakage in the system and cover gas could contaminate the sodium. An in-site purification system is necessary during the operation of the loop. The flow of purification by-pass is about 0.02 m<sup>3</sup>/h to 0.1 m<sup>3</sup>/h. The volume of cold trap is 0.01 m<sup>3</sup>. FIG. .5 shows the structure of the cold trap.




FIG. 5. Structure diagram of cold trap

**Sodium loading and drain system:** it consists storage tank and pipes and some valves. Storage tank is a "stomach" of the loop, which was located at the bottom of the whole systems. FIG. .6 shows the structure of the loading and drain system. The volume of storage is 0.06 m<sup>3</sup>.




FIG. 6. Diagram of sodium drain and loading system

**Cover gas and vacuum system:** The free surface of liquid sodium was covered by high purity argon during the operation of the loop. The argon need to be purified by gas purification system, which consists of Ar bottle, baffle tank, purifier, vacuum pump and sodium vapor trap, see FIG. .7.




FIG. .7 Diagram of cover gas and vacuum system

**Instrumentation and control system:** The function of instrumentation and control system are: 1) the temperature control and display; 2) the sodium flow control and display; 3) pressure display; 3) alarm on sodium level and over pressure

### Acceptance of radioactive material

No

### Scheme/diagram




FIG. 8. The diagram of HTMTSL

3D drawing/photo



FIG. 9. HTMTSL site

### Parameters table

Coolant inventory	125 kg
Power	Max 85 kW
Test sections	
TS #1	<u>Characteristic dimensions</u> inside diameter 44 mm Overall height →1000 mm
	<u>Static/dynamic experiment</u> Dynamic
	<u>Temperature range in the test section (Delta T)</u> 500°C-650°C
	<u>Operating pressure and design pressure</u> Operating Pressure →0.01MPa (gauge) Design pressure →0.2MPa
	<u>Flow range (mass, velocity, etc.)</u> The maximum sodium flow rate is 5 m <sup>3</sup> /h
TS #2	<u>Characteristic dimensions</u> inside diameter 44 mm Overall height →1000 mm
	<u>Static/dynamic experiment</u> Dynamic
	<u>Temperature range in the test section (Delta T)</u> 350°C-450°C
	<u>Operating pressure and design pressure</u> Operating Pressure →0.01MPa (gauge) Design pressure →0.2MPa
	<u>Flow range (mass, velocity, etc.)</u> The maximum sodium flow rate is 5 m <sup>3</sup> /h
Coolant chemistry measurement and control (active or not, measured parameters)	There is one cold traps in the circuit to guarantee the sodium purification process on line. The plugging temperature in the meter is lower than 120 °C when the circuit is on operation. The off-line measurement is available and the oxygen content dissolved in the sodium can be used and the limit for this loop is lower than 12ppm.
Instrumentation	Thermocouples, pressure transducer, Gas purification and injection system, flow meters

### COMPLETED EXPERIMENTAL CAMPAIGNS: MAIN RESULTS AND ACHIEVEMENTS

A first experimental campaign was conducted to verify the structural materials used for China Experimental Fast Reactor (CEFR) in 2000. The operation duration is 40 hours. No test was performed after that.

### PLANNED EXPERIMENTS (including time schedule)

No experiment is on the planning in near time..

### TRAINING ACTIVITIES

Training activities can be agreed with CIAE for the operation of the experimental campaign under the supervision of CIAE qualified staff.

**REFERENCES** (*specification of availability and language*)

[1] ZHANG D.D., High temperature sodium mass transfer test loop, *Chinese Journal of Nuclear Science and Engineering*, Vol.11, No.3, pp. 87-91, Sept. 1991. (In Chinese)

[2] ZHANG D.D., YAO Z.Y., LUO X.J. and et.al, The debugging and operation experience of high temperature sodium mass transfer loop, *Chinese Journal of Nuclear Science and Engineering*, Vol.15, No.4, pp. 47-53, Dec. 1995. (In Chinese)